

Interchangeability - Kompatibilität
RECTUS 27, CEJN 410, TST 410

Temperature Range-Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 500 PSI)

Flow capacity - Größen
NW - IO

Standard version - Standardversion
Buna N - Buna N
Nickel plated - Vernickelt



Options - Optionen
F - Straight through flow - ungehinderter Durchfluss
S - Stainless Steel - Edelstahl
V - Viton Seal - Viton Dichtung

For optional orders please add the symbol of your option end of the order no.
Optionsbestellungen Kennbuchstabe bitte hinzufügen (Beispiel: O27 EG I3-K-V)

Material - Material
Coupler Body - Kupplungsgrundkörper : Brass Nickel Plated - Messing Vernickelt
Back Part - Rückwärtiger Sleeve - Hülse : Brass Nickel Plated - Messing Vernickelt
: Steel Nickel Plated - Stahl vernickelt

Valve - Ventil : Brass - Messing
Springs - Federn : Stainless Steel - Edelstahl

Locking O-Ring - Sprengling : Stainless Steel - Edelstahl
Balls - Kugeln : Stainless Steel - Edelstahl AISI 420
Seals - Dichtungen : Buna (N) - Buna (N)
Plug - Nippel : Steel Nickel Plated - Stahl vernickelt



**SUPER FLOW LINE
SUPERDURCHFLUSS**



1800 l/mn


O27

**Couplings and Plugs
Kupplungen und Nippel**




Male Thread Couplings
Kupplungen mit Außengewinde

Connection Anschlüsse	Order No Bestellnr.	SW	Length Länge	Dia. Durchmesser
R 1/4"	O27 RG I3	24	63	28
R 3/8"	O27 RG I7	24	63	28
R 1/2"	O27 RG 2I	24	65	28
R 3/4"	O27 RG 26	27	65	28




Female Thread Couplings
Kupplungen mit Innengewinde

G 1/4"	O27 DG I3	24	57	28
G 3/8"	O27 DG I7	24	57	28
G 1/2"	O27 DG 2I	24	57	28
G 3/4"	O27 DG 26	30	58	28




Standard Hose Barb Couplings
Kupplungen mit Schlauchtülle

6 mm - 1/4"	O27 HG 06	24	75	28
8 mm - 5/16"	O27 HG 08	24	75	28
9 mm - 5/14"	O27 HG 09	24	75	28
10 mm - 3/8"	O27 HG IO	24	75	28
13 mm - 1/2"	O27 HG I3	24	75	28
16 mm - 5/8"	O27 HG I6	24	75	28
19 mm - 3/4"	O27 HG I9	24	75	28




Standard Hose Barb Plugs
Nippel mit Schlauchtülle

6 mm - 1/4"	O27 HU 06		48	
8 mm - 5/16"	O27 HU 08		48	
9 mm - 5/14"	O27 HU 09		48	
10 mm - 3/8"	O27 HU IO		48	
13 mm - 1/2"	O27 HU I3		48	
16 mm - 5/8"	O27 HU I6		48	
19 mm - 3/4"	O27 HU I9		48	



Male Thread Plugs
Nippel mit Außengewinde

R 1/4"	O27 RU I3	17	43	
R 3/8"	O27 RU I7	17	43	
R 1/2"	O27 RU 2I	22	48	
R 3/4"	O27 RU 26	27	50	



Female Thread Plugs
Nippel mit Innengewinde

G 1/4"	O27 DU I3	17	40	
G 3/8"	O27 DU I7	19	40	
G 1/2"	O27 DU 2I	24	46	
G 3/4"	O27 DU 26	32	46	